


Class 24(W)×K7 compacted strand



24(W)×K7

Nominal rope diameter	Approx. weight	Minimum breaking load			
		Rope grades, MPa			
		1570	1770	1960	2160
mm	kg/100m	kN	kN	kN	kN
8	31.4	41.2	46.4	51.4	56.7
9	39.7	52.1	58.8	65.1	71.7
10	49.0	64.4	72.6	80.4	88.6
12	70.6	92.7	104	116	128
14	96.0	126	142	158	174
16	125	165	186	206	227
18	159	209	235	260	287
20	196	257	290	321	354
22	237	312	351	389	429
24	282	371	418	463	510
26	331	435	491	543	599
28	384	505	569	630	694
30	441	579	653	723	797
32	502	659	743	823	907
34	566	744	839	929	1020
36	635	834	941	1040	—
38	708	930	1050	1160	—
40	784	1030	1160	1290	—
42	864	1140	1280	1420	—
44	949	1250	1400	1560	—
46	1040	1360	1540	1700	—

1 Total minimum breaking force of wire rope = Minimum breaking force x 1.287

LEADER OF ELEVATOR & CRANE WIRE ROPES

Jiangsu Safety Wire Rope Co., Ltd. was established in June 2005, with a registered capital of 34 million USD, and 582 employees. We went public on Shanghai Stock Exchange in China on March 31, 2016 with the stock code: 603028. The factory covers an area of 102,000 square meters and has an annual output of 80,000 tons of steel wire ropes. Our market share & industry rankings for elevator wire ropes are among the top 3 in China.