



Class 8×K26WS-PWRC(K) & 8×K36WS-PWRC(K) compacted strand & high performance



8×K26WS-PWRC(K)

8×K36WS-PWRC(K)

Nominal rope diameter	Approx. weight	Minimum breaking load		
		Rope grades, MPa		
		1770	1960	2160
mm	kg/100m	kN	kN	kN
12	75.3	124	137	151
13	88.4	145	161	177
14	103	169	187	206
15	118	194	214	236
16	134	220	244	269
17	151	249	275	303
18	169	279	309	340
19	189	311	344	379
20	209	344	381	420
21	231	379	420	463
22	253	416	461	508
23	277	455	504	555
24	301	495	549	605
25	327	538	595	656
26	354	582	644	710
27	381	627	694	765
28	410	674	747	823
29	440	723	801	883
30	471	774	857	945
32	536	881	975	1070
34	605	994	1100	1210
36	678	1110	1230	1360
38	755	1240	1380	1520
40	837	1380	1520	1680
42	923	1520	1680	1850
44	1010	1670	1840	2030
46	1110	1820	2020	2220
48	1200	1980	2190	2420
50	1310	2150	2380	2620
52	1410	2330	2580	2840
54	1530	2510	2780	3060
56	1640	2700	2990	3290
58	1760	2890	3200	3530
60	1880	3100	3430	3780

1 Total minimum breaking force of wire rope = Minimum breaking force x 1.250

LEADER OF ELEVATOR & CRANE WIRE ROPES

Jiangsu Safety Wire Rope Co., Ltd. was established in June 2005, with a registered capital of 34 million USD, and 582 employees. We went public on Shanghai Stock Exchange in China on March 31, 2016 with the stock code: 603028. The factory covers an area of 102,000 square meters and has an annual output of 80,000 tons of steel wire ropes. Our market share & industry rankings for elevator wire ropes are among the top 3 in China.